



# NPS-4.5-SM-W - Sensor Specification Sheet

## Technical Overview

<b>Range</b> – 3 km / 2 mi in urban areas	<b>Easy Maintenance Design</b>
<b>Battery Life</b> – Up to 10 years	<b>Small Package</b> – 205mm x 20mm
<b>Hassle Free Wireless Network</b> – we can provide and maintain the wireless infrastructure	<b>Streamlined Device Provisioning</b> – Most systems and APIs can be installed set up in under a day
<b>Parking Access Control</b> – <a href="#">SDI</a> technology for automated billing and priority access (US Patent awarded)	<b>Accurate Detection in most Challenging Operational Environments</b> – small vehicles, EVs, EMI, rain, dirt/mud, snow (wet and dry)
<b>Easy and Secure Configuration</b> – calibration and firmware updates through mobile app (via Bluetooth)	<b>Vehicle Detection accuracy and speed</b> – 99.9% under 7 seconds detection time
<b>Applications</b> – Per-space vehicle detection and aggregate ingress / egress per lane vehicle counting	



## Technical Specification

<b>Installation Method</b>	Adhesive or screw anchors
<b>Load Resistance</b>	< 5,000 kg per wheel
<b>Dimensions</b>	Dia. 205 mm, Height 20 mm / Dia. 8 5/64", Height 3/4"
<b>Enclosure</b>	UV-stabilized polycarbonate, IP68, IPx9K, Black (default)
<b>Operating Temperature</b>	-40 C to +85 C, 0-100% humidity
<b>LPWAN Radio</b>	Weightless-N, SigFox, LoRaWAN 1.0.3 Class A
<b>Communication Range</b>	Up to 3 km / 2 mi Urban, up to 6 km / 4 mi in Rural
<b>Communication Frequency</b>	ISM bands – US: 902-928 MHz, EU/UK: 865-868 MHz, AU: 915-928 MHz
<b>Bluetooth Protocol</b>	v. 5.1 standard + Secure Driver Identification (SDI)
<b>Battery Life</b>	9-10 years @ 20 parking sessions per day
<b>Battery Type</b>	10,800mAh, Li-SOCI2 primary cell, replaceable