

# PILOT

Energy Monitoring | Indoor Air Quality

Temperature, Humidity



**Pilot** is a connected sensor for measuring temperature and relative humidity.

Thanks to its many features and advanced technical configuration possibilities, this IoT sensor meets all the requirements of professionals in commercial and residential buildings.

**Pilot** integrates the iZiAiR air quality and hygrothermal comfort algorithm to easily study each indoor environment and identify possible improvements.

Thanks to its wireless communication module, data can be accessed remotely, simply from a smartphone or a computer screen\*.

## PRODUCT BENEFITS

- Lithium batteries, autonomy 10 years \*\*: no repeated battery change, no electrical connection required
- Fully configurable locally by NFC or remotely by downlink
- Design and compact to fit into any interior
- Robust product totally sealed and cannot be dismantled
- Anti-theft fixing device for wall mounting
- Quick and easy installation
- No maintenance required

## APPLICATIONS

- Monitoring of ambient parameters in commercial and residential buildings

\* Optional subscription fees may apply \*\* Lifetime for standard use. Battery life may vary

**UNITRONIC**

UNITRONIC GmbH  
Hellersbergstraße 10a  
41460 Neuss

Telefon 02131 – 7529180  
Telefax 02131 – 75291850  
info@unitronic.de

PART OF  
**LAGERCRANTZ GROUP**



# PILOT

## FUNCTIONS

- Measurement of ambient parameters
  - o Temperature
  - o Relative humidity
- Central button
  - o Short press: programmable action
  - o Long press: instantaneous measurement and transmission
- Configuration and diagnostics of the product locally (NFC) or remotely (downlink)
- **iZiAIR** Indoor Air Quality Index



Very good



Average

## SPECIFICATIONS

### Temperature

Resolution: 0.1°C

Accuracy: ±0.3°C

Measurement range: -30°C / +70°C

### Humidity

Resolution: 0.5% R.H.

Accuracy: ±2% R.H.

Measurement range: 0 - 100% R.H.

### Frequency of measurements

- Every 10 minutes (configurable)

### Data transmission mode

- Real time
- Datalog (gather measurements in a single message)
- Alerts on threshold

### Network pairing / Operation / CO<sub>2</sub> indicator

3x LED: Green / Orange / Red

### Power supply

3x integrated lithium batteries (5850 mAh)

### Battery life

10 years in typical use

**Dimensions:** 105 x 105 x 30 mm

**Weight:** 120g

### Conditions of use

Indoor environment

Temperature: 0°C to + 50°C

Relative humidity: 0% RH to 95% RH

### Type of mounting

Wall-mounted

### Wireless protocol

- LoRaWAN (868 MHz)

- Sigfox (RC1)

- EnOcean (868 MHz)

*Other wireless protocols studied on request*

## PRODUCT REFERENCES

**Pilot (LoRaWAN)** : I880LR\_FND\_S

**Pilot (Sigfox)** : I880SF\_FND\_S

**Pilot (EnOcean)** : I880EO\_FND\_S

## CONTENT OF THE BOX

- 1 device
- 1 anti-theft wall bracket
- 2 screws and nylon wall plugs
- 3M® double-sided adhesive attachment

## CERTIFICATION

CE